
TP-LINK®

China's No.1
TP-LINK
China's No.1
Market Share Holder



10/100 FAST ETHERNET PCI ADAPTER

ACCESS THE INTERNET

Connect to a network and surf the web with your desktop PC

AUTO DETECTION

Windows® automatically detects the adapter for easy installation





RELIABLE WIRED NETWORKING

The TP-Link 10/100 Fast Ethernet PCI Adapter (TL-3239DL) delivers reliable wired network connectivity for your desktop PC. Access a high-speed Internet connection through your wired network using this Ethernet PCI Adapter and surf the web, check e-mail, share documents, music, and photos.

EASY TO INSTALL AND USE

This Fast Ethernet PCI Adapter is automatically detected by Windows® during installation, simplifying the setup process. It supports IEEE 802.3 and 802.3u, ensuring compatibility with 10BASE-T and 100BASE-TX networks. This Ethernet Desktop Adapter utilizes auto-negotiation to automatically adjust to the highest supported transfer rate (up to 200Mbps in full duplex mode).

The TP-Link 10/100 Fast Ethernet PCI Adapter (TL-3239DL) is a simple, cost-effective solution for desktop computers, making it the ideal choice for wired home networking applications.

WHAT THIS PRODUCT DOES

Connect to your wired home network by adding a D-Link 10/100 Fast Ethernet Desktop Adapter to your desktop computer. Once connected, you can share a high-speed Internet connection while also getting access to shared documents, music, and photos from other computers on your network.

TECHNICAL SPECIFICATIONS

STANDARDS	• IEEE 802.3 10Base-T Ethernet • IEEE 802.3u 100Base-TX Fast Ethernet • ANSI/IEEE 802.3 NWay Auto-Negotiation • IEEE 802.3x Full Duplex Flow Control Support
NETWORK DATA TRANSFER RATE	• Ethernet: 10Mbps (Half-duplex) • Ethernet: 20Mbps (Full-duplex) • Fast Ethernet: 100Mbps (Half-duplex) • Fast Ethernet: 200Mbps (Full-duplex)
FEATURES	• PCI Local Bus Master 2.1/2.2 Support

	• Plug-and-Play Installation • Diagnostics support
PROTOCOL	CSMA/CD
NETWORK MEDIA	• Ethernet: UTP Cat3, 4, 5 EIA/TIA-568 100-ohm screened twisted-pair (STP) • Fast Ethernet: UTP Cat5, EIA/TIA-568 100-ohm screened twisted-pair (STP)
LED	Link/Act
CERTIFICATIONS	• FCC • CE
OPERATING TEMPERATURE	0℃~40℃ (32℉~104℉)
OPERATING HUMIDITY	10%~90% (non-condensing)
DIMENSIONS	134 x 121 x 22 mm (5.3 x 4.8 x 0.9 in.)

MINIMUM SYSTEM REQUIREMENTS

- ✧ Windows 98/ME/NT4.0/2000/2003/XP, Netware, Linux
- ✧ 32-bit PCI slot

1. Latest software and documentation are available at http://www.tp-link.com.
2. All references to speed are for comparison purposes only. Product specifications, size, and shape are subject to change without notice, actual product appearance may differ than that depicted herein.

Specifications are subject to change without notice. TP-LINK® is a registered trademark of TP-LINK Technologies Co., Ltd. Other brands and product names are trademarks or registered trademarks of their respective holders. No part of the specifications may be reproduced in any form or by any means or used to make any derivative such as translation, transformation, or adaptation without permission from TP-LINK Technologies Co., Ltd. Copyright © 2006 TP-LINK Technologies Co., Ltd. All rights reserved.