



AM3+ CPU support ready

# ASUS

## M5A78L-M LX Sales Kit

Entry-level AMD 760G(780L)/SB710 motherboard for AM3+ Platform



- EPU
- Turbo Key
- Anti-surge
- Core Unlocker

# SPEC Table: M5A78L-M LX

|                        |  |
|------------------------|--|
| <b>CPU</b>             | AMD® Socket AM3+ for FX™ /Phenom™ II /Athlon™ II /Sempron™ 100 Series Processors   |
| <b>Chipset</b>         | AMD® 760G (780L) / SB710   |
| <b>System Bus</b>      | HyperTransport™ 3.0, Up to 5200 MT/s   |
| <b>Memory</b>          | 2 x DIMM, Max. 16 GB, DDR3 1866(O.C.)* / 1600(O.C.)* / 1333/1066 ECC, Non-ECC and Unbuffered Memory                        |
| <b>VGA</b>             | Integrated ATI Radeon 3000<br>Maximum shared memory of 1GB<br>Supports Microsoft® DirectX 10<br>Hybrid CrossFireX™ Support |
| <b>Expansion slots</b> | 1 x PCIe 2.0 x 16 slot;<br>2 x PCIe 2.0 x 1 slots;<br>1 x PCI slot   |
| <b>Storage</b>         | 6 x SATA 3Gb/s;  |
| <b>USB</b>             | 10 x USB 2.0/1.1 ports<br>(6 ports at mid-board, 4 ports at back panel)  |
| <b>Audio</b>           | 3 Jack , 8 CH  |
| <b>LAN</b>             | Realtek Gb LAN   |
| <b>Form Factor</b>     | µATX (24.4cm x 20.3cm)   |



\*\*AMD® 100 and 200 series CPU support up to DDR3 1066MHz.

\*\*AMD® FX Series CPU on this motherboard supports up to DDR3 1866MHz as its standard memory frequency.

\*\* Refer to [www.asus.com](http://www.asus.com) or user manual for Memory QVL (Qualify Vendor List)

# Product Overview

