HDS-4P

4-PORT HDMI SPLITTER



4-Port HDMI Splitter

Connect One HDMI/HDTV Component to Four Displays

The HDS-4P is a 4-port HDMI splitter capable of connecting one HDMI/HDTV output to four displays.


- HDMI 1.3c and DVI 1.0 compliant
- HDCP 1.2 compliant
- Wide Frequency Range: 25MHz~225MHz
- Video bandwidth: 6.7GBPS
- Resolution up to 1080p or WUXGA
- Supports CEC (not bypassing)
- Supports Dolby Digital, DTS-HD and Dolby True HD audio
- Easy installation

Smart-AVI
SMART AUDIO VIDEO INNOVATION

Made in the USA

www.smartavi.com

SPECIFICATIONS



Application Diagram

VIDEO	
Format	HDMI 1.3c [Deep Color, xvYcc color space supported]
DVI Compliance	DVI 1.1
HDCP Compliance	Yes
Video Bandwidth	Single-link 225MHz [6.75Gbps]
Resolution	Up to WUXGA [1920x1200 @ 60Hz] & UXGA [1600x1200 @ 60Hz]
Input Interface	(1) HDMI[7.1ch audio & video]
Output Interface	(4) HDMI[7.1ch audio & video]
Connector	Type A[19-pin male]
AUDIO	
Supported Formats	DTS-HD Master Audio, Dolby TrueHD Dolby Digital, DTS, DVD-Audio, LPCM, SACD, MPCM
OTHER	
DDC Signal	5 Volts [peak-to-peak], TTL
TDMS Signal	1.2 Volts[peak-to-peak], TTL
Power	External 5VDC2A
Dimensions	6.5"W x 1.125"H x 3"D
Weight	0.35 lbs.
Approvals	Device: CE, ROHS Power Supply: C-UL US, CE

ORDERING INFORMATION	
Part No.	Description
HDS-4PS	HDMI 4-Port Splitter. Includes: [HDS4P and PS5VDC2A]



HDS-4P Front



HDS-4P Rear

Many leading companies have recognized and embraced the innovation of SmartAVI's technologies and have successfully incorporated them into their organizations. Users of SmartAVI include:



Smart-AVI
SMART AUDIO VIDEO INNOVATION

SmartAVI, Inc. / Twitter: smartavi - 2840 N. Naomi Ave. Burbank, CA 91504 - Tel: (818) 565-0011 Fax: (818) 565-0020 - http://www.SmartAVI.com